

## TYRES

Product group	Tyres
Item number	15772538
Valid tyre size	14.9 - 24
LI / SI / PR	145 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	AT 625



## Notes and features

- Tread pattern for excellent traction on difficult terrain
- Additional tread blocks in between the main blocks provide for better puncture resistance
- Good mileage through the use of a wear- and cut-resistant tread compound
- Suitable for backhoe loaders, earthmovers and similar vehicles

## Technical Informations

Item number	15772538
EAN	8903094041367
Valid tyre size	14.9 - 24
LI / SI / PR	145 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	AT 625
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	71,43
Recommended rim size	DW13
Permitted rim size	DW11, DW12, DW13L
Maximum air pressure [bar].	2,90
Section width (mm)	400
Outer diameter of tyre [mm].	1265
Stat. radius (SLR) [mm]	575
Rolling circumference [mm].	3800
Tread depth (mm)	33,0
Number of lugs	23x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		2,90	