

TYRES

Product group	Tyres
Item number	15772539
Valid tyre size	16.9 - 28
LI / SI / PR	152 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	AT 625



Notes and features

- Tread pattern for excellent traction on difficult terrain
- Additional tread blocks in between the main blocks provide for better puncture resistance
- Good mileage through the use of a wear- and cut-resistant tread compound
- Suitable for backhoe loaders, earthmovers and similar vehicles

Technical Informations

Item number	15772539
EAN	8903094040315
Valid tyre size	16.9 - 28
LI / SI / PR	152 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	AT 625
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	91,43
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	2,60
Section width (mm)	450
Outer diameter of tyre [mm].	1415
Stat. radius (SLR) [mm]	645
Rolling circumference [mm].	4254
Tread depth (mm)	35,0
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,60	