

TYRES

Product group	Tyres
Item number	15772541
Valid tyre size	400 / 70 - 20
LI / SI / PR	156 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	15772541
EAN	8903094051823
Valid tyre size	400 / 70 - 20
Alternative size 1	16.0/70-20
LI / SI / PR	156 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	67,97
Recommended rim size	13
Permitted rim size	12SDC, 13SDC, 14
Maximum air pressure [bar].	5,00
Section width (mm)	405
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	501
Rolling circumference [mm].	3303
Tread depth (mm)	33,5
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		5,00	