

TYRES

Product group	Tyres
Item number	15772550
Valid tyre size	14.00 - 24
LI / SI / PR	147 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Trac Grader +



Notes and features

- Robust tread pattern design for drive wheels in off-road use.
- The hard-wearing casing and a special tread compound with weather- and ozone-resistant characteristics as well as optimum resistance.
- to cuts and impacts guarantee a long tyre life in the toughest operating conditions.
- Ideal for graders.

Technical Informations

Item number	15772550
EAN	8903094014606
Valid tyre size	14.00 - 24
LI / SI / PR	147 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	Trac Grader +
TRA Code	G2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	77,57
Recommended rim size	8.00TG SDC
Permitted rim size	9.00/1.5(DC), 10.00VA SDC, 10.00WA SDC
Maximum air pressure [bar].	2,75
Section width (mm)	364
Outer diameter of tyre [mm].	1348
Stat. radius (SLR) [mm]	598
Rolling circumference [mm].	3990
Tread depth (mm)	25,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		2,75	