

TYRES

Product group	Tyres
Item number	15772568
Valid tyre size	16.9 - 24
LI / SI / PR	149 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621



Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on backhoe loaders, wheel loaders and similar vehicles.

Technical Informations

Item number	15772568
EAN	8903094035397
Valid tyre size	16.9 - 24
LI / SI / PR	149 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	86,15
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	2,60
Section width (mm)	450
Outer diameter of tyre [mm].	1302
Stat. radius (SLR) [mm]	590
Rolling circumference [mm].	3906
Tread depth (mm)	30,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		2,60	