

TYRES

Product group	Tyres
Item number	15772570
Valid tyre size	17.5 L - 24
LI / SI / PR	148 A6, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459



Notes and features

- The strong nylon carcass & the special rubber compound make the tyre particularly resistant to breaks, punctures & similar damage.
- Extra wide and overlapping lugs in the center of the tread.
- Ideal for industrial use such as on backhoe loaders.

Technical Informations

Item number	15772570
EAN	8903094016594
Valid tyre size	17.5 L - 24
LI / SI / PR	148 A6, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	70,20
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	2,70
Section width (mm)	445
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	557
Rolling circumference [mm].	3825
Tread depth (mm)	27,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A6	3150	30		2,70	