

TYRES

Product group	Tyres
Item number	15772580
Valid tyre size	19.5 L - 24
LI / SI / PR	151 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459



Notes and features

- The strong nylon carcass & the special rubber compound make the tyre particularly resistant to breaks, punctures & similar damage.
- Extra wide and overlapping lugs in the center of the tread.
- Ideal for industrial use such as on backhoe loaders.

Technical Informations

Item number	15772580
EAN	8903094016686
Valid tyre size	19.5 L - 24
Alternative size 1	500/70-24
LI / SI / PR	151 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	94,24
Recommended rim size	DW16L
Maximum air pressure [bar].	2,30
Section width (mm)	490
Outer diameter of tyre [mm].	1333
Stat. radius (SLR) [mm]	585
Rolling circumference [mm].	4031
Tread depth (mm)	27,5
Number of lugs	15x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		2,30	