

TYRES

Product group	Tyres
Item number	15772588
Valid tyre size	16.9 - 28
LI / SI / PR	152 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 463



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT TR 463 is designed for use on backhoe loaders and industrial tractors.
- Its high-quality rubber compound and strong nylon carcass guarantee the best properties for industrial and OTR use as well as on construction sites.
- When used as a driven wheel, the tyre provides very good traction.

Technical Informations

Item number	15772588
EAN	8903094053339
Valid tyre size	16.9 - 28
LI / SI / PR	152 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 463
TRA Code	R4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	90,44
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	2,60
Section width (mm)	450
Outer diameter of tyre [mm].	1405
Stat. radius (SLR) [mm]	636
Rolling circumference [mm].	4190
Tread depth (mm)	27,5
Number of lugs	23x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,60	