

## TYRES

Product group	Tyres
Item number	15772590
Valid tyre size	21 L - 24
LI / SI / PR	155 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459



## Notes and features

- The strong nylon carcass & the special rubber compound make the tyre particularly resistant to breaks, punctures & similar damage.
- Extra wide and overlapping lugs in the center of the tread.
- Ideal for industrial use such as on backhoe loaders.

## Technical Informations

Item number	15772590
EAN	8903094016709
Valid tyre size	21 L - 24
LI / SI / PR	155 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 459
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	108,41
Recommended rim size	DW18L
Maximum air pressure [bar].	2,20
Section width (mm)	533
Outer diameter of tyre [mm].	1378
Stat. radius (SLR) [mm]	605
Rolling circumference [mm].	3995
Tread depth (mm)	29,0
Number of lugs	15x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		2,20	