

TYRES

Product group	Tyres
Item number	15772591
Valid tyre size	440 / 80 - 24
LI / SI / PR	168 A8, 22 PR
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	15772591
EAN	8903094042067
Valid tyre size	440 / 80 - 24
Alternative size 1	17.0/80-24
LI / SI / PR	168 A8, 22 PR
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	97,80
Recommended rim size	DW14L
Permitted rim size	DW13, DW13L, DW15L
Maximum air pressure [bar].	5,00
Section width (mm)	455
Outer diameter of tyre [mm].	1315
Stat. radius (SLR) [mm]	610
Rolling circumference [mm].	3986
Tread depth (mm)	33,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		5,00	