

TYRES

Product group	Tyres
Item number	15772592
Valid tyre size	400 / 80 - 24
LI / SI / PR	162 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	15772592
EAN	8903094040599
Valid tyre size	400 / 80 - 24
Alternative size 1	15.5/80-24
LI / SI / PR	162 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,86
Recommended rim size	DW13
Permitted rim size	DW12, DW13L, DW14L
Maximum air pressure [bar].	5,80
Section width (mm)	405
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	570
Rolling circumference [mm].	3781
Tread depth (mm)	34,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		5,80	