

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15772593 |
| Valid tyre size | 16.9 - 30 |
| LI / SI / PR | 153 A8, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | TR 459 |



Notes and features

- The strong nylon carcass & the special rubber compound make the tyre particularly resistant to breaks, punctures & similar damage.
- Extra wide and overlapping lugs in the center of the tread.
- Ideal for industrial use such as on backhoe loaders.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15772593 |
| EAN | 8903094035595 |
| Valid tyre size | 16.9 - 30 |
| LI / SI / PR | 153 A8, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | TR 459 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 90,57 |
| Recommended rim size | DW15L |
| Permitted rim size | DW14L |
| Maximum air pressure [bar]. | 2,60 |
| Section width (mm) | 440 |
| Outer diameter of tyre [mm]. | 1470 |
| Stat. radius (SLR) [mm] | 657 |
| Rolling circumference [mm]. | 4484 |
| Tread depth (mm) | 28,0 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 153 A8 | 3650 | 40 | | 2,60 | |