

TYRES

Product group	Tyres
Item number	15772594
Valid tyre size	400 / 70 - 24
LI / SI / PR	158 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	15772594
EAN	8903094051977
Valid tyre size	400 / 70 - 24
Alternative size 1	16.0/70-24
LI / SI / PR	158 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	78,56
Recommended rim size	13
Permitted rim size	DW12, 13SDC, DW13, DW13L, DW14L
Maximum air pressure [bar].	5,00
Section width (mm)	395
Outer diameter of tyre [mm].	1175
Stat. radius (SLR) [mm]	544
Rolling circumference [mm].	3556
Tread depth (mm)	33,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		5,00	