

TYRES

Product group	Tyres
Item number	15772597
Valid tyre size	16.9 - 30
LI / SI / PR	153 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621



Notes and features

- Excellent traction in difficult terrain.
- Wide tread blocks increase puncture resistance.
- Good mileage through the use of a wear and cut-resistant rubber compound
- For use on backhoe loaders, wheel loaders and similar vehicles.

Technical Informations

Item number	15772597
EAN	8903094027507
Valid tyre size	16.9 - 30
LI / SI / PR	153 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AT 621
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	100,31
Recommended rim size	DW15L
Permitted rim size	DW14L
Maximum air pressure [bar].	2,60
Section width (mm)	450
Outer diameter of tyre [mm].	1460
Stat. radius (SLR) [mm]	670
Rolling circumference [mm].	4398
Tread depth (mm)	30,0
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		2,60	