

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15772598 |
| Valid tyre size | 500 / 70 - 24 |
| LI / SI / PR | 164 A8 |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Con Star |



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15772598 |
| EAN | 8903094051731 |
| Valid tyre size | 500 / 70 - 24 |
| Alternative size 1 | 19.5L-24 |
| LI / SI / PR | 164 A8 |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Con Star |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 110,87 |
| Recommended rim size | DW16L |
| Permitted rim size | DW15L, DW18L |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 505 |
| Outer diameter of tyre [mm]. | 1300 |
| Stat. radius (SLR) [mm] | 579 |
| Rolling circumference [mm]. | 3926 |
| Tread depth (mm) | 33,5 |
| Number of lugs | 16x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 164 A8 | 5000 | 40 | | 4,00 | |