

TYRES

Product group	Tyres
Item number	15772599
Valid tyre size	480 / 80 - 26
LI / SI / PR	160 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	15772599
EAN	8903094052813
Valid tyre size	480 / 80 - 26
Alternative size 1	18.4-26
LI / SI / PR	160 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	117,04
Recommended rim size	DW15L
Permitted rim size	DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	490
Outer diameter of tyre [mm].	1410
Stat. radius (SLR) [mm]	643
Rolling circumference [mm].	4272
Tread depth (mm)	33,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,20	