

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 15772621 |
| Valid tyre size | 14.00 - 24 |
| LI / SI / PR | 168 B / 188 A2, 28 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | EM 937 |



Notes and features

- The BKT EM 937 E-3 (IND) was specially developed for stacking and loading operations in ports.
- Its cut-resistant rubber compound is extremely durable and guarantees a long service life.
- Only permitted for mounting on standard flat base rim.

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15772621 |
| EAN | 8903094015375 |
| Valid tyre size | 14.00 - 24 |
| LI / SI / PR | 168 B / 188 A2, 28 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | EM 937 |
| TRA Code | E3/L3 |
| Carcass properties | HD |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 142,68 |
| Recommended rim size | 10.00W |
| Maximum air pressure [bar]. | 9,25 |
| Section width (mm) | 375 |
| Outer diameter of tyre [mm]. | 1368 |
| Stat. radius (SLR) [mm] | 628 |
| Rolling circumference [mm]. | 4050 |
| Tread depth (mm) | 26,5 |
| Number of lugs | 34x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 168 B | 5600 | 50 | | 6,50 | |
| 188 A2 | 10000 | 10 | | 9,25 | |