Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15772622
Valid tyre size	14.00 - 24
LI / SI / PR	28 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	EM 937 WA



Notes and features

- The BKT EM 937 E-3 (IND) was specially developed for • stacking and loading operations in ports.
- Its cut-resistant rubber compound is extremely durable ٠ and guarantees a long service life.
- Due to its bead construction, the special WA version is • intended to be mounted on 5° tapered rims.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15772622
EAN	8903094043996
Valid tyre size	14.00 - 24
LI / SI / PR	28 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	EM 937 WA
TRA Code	IND3
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	143,20
Recommended rim size	10.00WA
Permitted rim size	10.00VA
Maximum air pressure [bar].	10,00
Section width (mm)	375
Outer diameter of tyre [mm].	1368
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4050
Tread depth (mm)	26,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	12500	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.