

TYRES

Product group	Tyres
Item number	15772626
Valid tyre size	14.00 - 24
LI / SI / PR	28 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rock Grip WA





Notes and features

- The Rock Grip Port (IND-4) from BKT is an earthmoving tyre with extra deep and robust tread pattern lugs, especially for use in ports.
- The strong casing with the low-wear tread compound ensures a long service life, even wear and high stability.
- Most suitable for use on container stackers, reach stackers and similar vehicles.
- Due to its bead construction, the special WA version is intended to be mounted on 5° tapered rims.



Technical Informations

Item number	15772626
EAN	8903094049752
Valid tyre size	14.00 - 24
LI / SI / PR	28 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rock Grip WA
TRA Code	IND4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	188,89
Recommended rim size	10.00WA
Permitted rim size	10.00VA
Maximum air pressure [bar].	10,00
Section width (mm)	375
Outer diameter of tyre [mm].	1410
Stat. radius (SLR) [mm]	647
Rolling circumference [mm].	4173
Tread depth (mm)	50,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	12500	25		10,00	
	13500	10		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.