

TYRES

Product group	Tyres
Item number	15772638
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54



Notes and features

- The smooth and extra deep L-4S tread pattern is ideally suited to handling empty and loaded containers, especially on hard surfaces.
- The tread pattern consists of a highly wear- and cut-resistant rubber compound.
- Due to its extra deep, smooth tread pattern design, the tyre offers excellent ride comfort and outstanding stability in lift mode.

Technical Informations

Item number	15772638
EAN	8903094015634
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54
TRA Code	L4S
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	444,23
Recommended rim size	13.00/2.5
Maximum air pressure [bar].	10,30
Section width (mm)	528
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	750
Rolling circumference [mm].	4880
Tread depth (mm)	59,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	22400	10		10,30	