Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15772641
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Container King



Notes and features

- The wide central rib creates a large contact surface and provides for outstanding stability when lifting heavy weights
- The strong casing and special hard-wearing running surface compound provide for excellent durability and a long service life
- Best suited for container handlers, such as reach stackers

20.09.2024

Bohnenkamp Moving Professionals

Technical Informations

Item number	15772641
EAN	8903094036516
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Container King
TRA Code	IND4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	422,25
Recommended rim size	13.00/2.5
Permitted rim size	15.00/2.5
Maximum air pressure [bar].	10,00
Section width (mm)	528
Outer diameter of tyre [mm].	1675
Stat. radius (SLR) [mm]	765
Rolling circumference [mm].	4955
Tread depth (mm)	68,0
Number of lugs	29x2
E-Ready	No

Load capacity

Ind	Ex Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	22950	10		10,00	

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.