

TYRES

Product group	Tyres
Item number	15772643
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Rock Grip



Notes and features

- The Rock Grip Port (IND-4) from BKT is an earthmoving tyre with extra deep and robust tread pattern lugs, especially for use in ports.
- The strong casing with the low-wear tread compound provides a long service life, even wear and high stability.
- Most suitable for use on container stackers, reach stackers and similar vehicles.
- Only permitted for mounting on standard flat base rim.



Technical Informations

Item number	15772643
EAN	8903094015528
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rock Grip
TRA Code	E4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	370,18
Recommended rim size	13.00/2.5
Permitted rim size	15.00/2.5
Maximum air pressure [bar].	9,50
Section width (mm)	510
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	753
Rolling circumference [mm].	4885
Tread depth (mm)	55,0
Number of lugs	30x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	9750	50		7,00	
	17000	10		9,50	