

## **TYRES**

Product group	Tyres
Item number	15772644
Valid tyre size	21.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	XL Grip



## **Notes and features**

- The BKT XL-Grip is a non-directional tyre with a wide, robust tread pattern design.
- A special silica tread compound and a hard-wearing nylon casing ensure the best possible resistance against cuts and impact damage.
- The BKT XL-Grip Series is suitable for numerous vehicles and uses.



## **Technical Informations**

Item number         15772644           EAN         8903094026708           Valid tyre size         21.00 - 25           LI / SI / PR         40 PR           TL/TT         TL           Brand         BKT           Tread pattern         XL Grip           TRA Code         IND3           Antistatic         No           Tyre colour         Black           ECE regulation number         not necessary           Nettogewicht [kg] (gültig)         452,36           Recommended rim size         15.00/3.0           Maximum air pressure [bar].         9,90
Valid tyre size 21.00 - 25  LI / SI / PR 40 PR  TL/TT TL  Brand BKT  Tread pattern XL Grip  TRA Code IND3  Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
LI/SI/PR 40 PR  TL/TT TL  Brand BKT  Tread pattern XL Grip  TRA Code IND3  Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0
TL/TT TL  Brand BKT  Tread pattern XL Grip  TRA Code IND3  Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
Brand BKT  Tread pattern XL Grip  TRA Code IND3  Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
Tread pattern XL Grip  TRA Code IND3  Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
TRA Code IND3  Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
Antistatic No  Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
Tyre colour Black  ECE regulation number not necessary  Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
ECE regulation number     not necessary       Nettogewicht [kg] (gültig)     452,36       Recommended rim size     15.00/3.0       Permitted rim size     17.00/3.0
Nettogewicht [kg] (gültig) 452,36  Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
Recommended rim size 15.00/3.0  Permitted rim size 17.00/3.0
Permitted rim size 17.00/3.0
Maximum air pressure [bar]. 9.90
and the second second second second
Section width (mm) 576
Outer diameter of tyre [mm]. 1750
Stat. radius (SLR) [mm] 789
Rolling circumference [mm]. 5185
Tread depth (mm) 36,0
Number of lugs 28x2
E-Ready No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	27810	10		9,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.