

## TYRES

Product group	Tyres
Item number	15772645
Valid tyre size	15.5 - 25
LI / SI / PR	162 A2 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288



## Notes and features

- Solid tyre with robust tread pattern for powered wheels for off-road use
- The tyre features hard casing and a special weather and ozone resistant rubber compound for the running surface as well as first-rate protection from cutting and impact damage
- The open tread pattern design allows for good traction and self-cleaning properties
- Suitable for use on loaders & graders

## Technical Informations

Item number	15772645
EAN	8903094014415
Valid tyre size	15.5 - 25
LI / SI / PR	162 A2 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	78,60
Recommended rim size	12.00/1.3
Permitted rim size	12.00/1.3(DC)
Maximum air pressure [bar].	4,00
Section width (mm)	385
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	572
Rolling circumference [mm].	3772
Tread depth (mm)	24,0
Number of lugs	22x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A2	4750	10		4,00	
142 A8	2650	40		2,50	