

TYRES

Product group	Tyres
Item number	15772647
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	Port King Classic



Notes and features

- The BKT Port King Classic is a port tyre and was specially developed for vehicles in container handling.
- Due to its rugged nylon casing, the tyre is especially protected against piercing, cracks and punctures.
- Its rubber compound is extremely low-wear and provides excellent stability in lifting mode at very high loading capacities.

Technical Informations

Item number	15772647
EAN	8903094054480
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	Port King Classic
TRA Code	IND4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	412,25
Recommended rim size	13.00/2.5
Permitted rim size	15.00/2.5
Maximum air pressure [bar].	10,00
Section width (mm)	528
Outer diameter of tyre [mm].	1675
Stat. radius (SLR) [mm]	765
Rolling circumference [mm].	4955
Tread depth (mm)	67,5
Number of lugs	29x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	22950	10		10,00	
	21250	25		10,00	