

TYRES

Product group	Tyres
Item number	15772654
Valid tyre size	17.5 - 25
LI / SI / PR	150 A8 / 177 A2, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288



Notes and features

- Solid tyre with robust tread pattern for powered wheels for off-road use
- The tyre features hard casing and a special weather and ozone resistant rubber compound for the running surface as well as first-rate protection from cutting and impact damage
- The open tread pattern design allows for good traction and self-cleaning properties
- Suitable for use on loaders & graders

Technical Informations

Item number	15772654
EAN	8903094014439
Valid tyre size	17.5 - 25
LI / SI / PR	150 A8 / 177 A2, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	94,69
Recommended rim size	14.00/1.5
Permitted rim size	14.00/1.3(DC)
Maximum air pressure [bar].	4,80
Section width (mm)	445
Outer diameter of tyre [mm].	1330
Stat. radius (SLR) [mm]	596
Rolling circumference [mm].	3950
Tread depth (mm)	26,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		2,75	
177 A2	7300	10		4,80	