

## TYRES

Product group	Tyres
Item number	15772662
Valid tyre size	20.5 - 25
LI / SI / PR	156 A8 / 181 A2, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288



## Notes and features

- Solid tyre with robust tread pattern for powered wheels for off-road use
- The tyre features hard casing and a special weather and ozone resistant rubber compound for the running surface as well as first-rate protection from cutting and impact damage
- The open tread pattern design allows for good traction and self-cleaning properties
- Suitable for use on loaders & graders

## Technical Informations

Item number	15772662
EAN	8903094014446
Valid tyre size	20.5 - 25
LI / SI / PR	156 A8 / 181 A2, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	151,86
Recommended rim size	17.00/2.0
Permitted rim size	17.00/1.7
Maximum air pressure [bar].	3,50
Section width (mm)	520
Outer diameter of tyre [mm].	1480
Stat. radius (SLR) [mm]	656
Rolling circumference [mm].	4396
Tread depth (mm)	29,0
Number of lugs	21x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		2,20	
181 A2	8250	10		3,50	