

TYRES

Product group	Tyres
Item number	15772671
Valid tyre size	23.5 - 25
LI / SI / PR	20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Loader Plus



Bohnenkamp
Moving Professionals



Notes and features

- The BKT Loader Plus is an EM diagonal tyre for wheel loaders and similar vehicles.
- Its sturdy rubber compound optimally protects the tyre from damages through cuts and punctures.
- The tyre offers good traction and a long service life.

Technical Informations

Item number	15772671
EAN	8903094065035
Valid tyre size	23.5 - 25
LI / SI / PR	20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Loader Plus
TRA Code	L3
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	241,47
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	3,75
Section width (mm)	600
Outer diameter of tyre [mm].	1640
Stat. radius (SLR) [mm]	749
Rolling circumference [mm].	4855
Tread depth (mm)	33,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	10900	10		3,75	