

TYRES

Product group	Tyres
Item number	15772674
Valid tyre size	23.5 - 25
LI / SI / PR	167 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288



Notes and features

- Solid tyre with robust tread pattern for powered wheels for off-road use
- The tyre features hard casing and a special weather and ozone resistant rubber compound for the running surface as well as first-rate protection from cutting and impact damage
- The open tread pattern design allows for good traction and self-cleaning properties
- Suitable for use on loaders & graders

Technical Informations

Item number	15772674
EAN	8903094014460
Valid tyre size	23.5 - 25
LI / SI / PR	167 A8, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	GR 288
TRA Code	L2/G2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	202,81
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	3,75
Section width (mm)	595
Outer diameter of tyre [mm].	1610
Stat. radius (SLR) [mm]	708
Rolling circumference [mm].	4782
Tread depth (mm)	31,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	487
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		2,50	
	10900	10		3,75	