

TYRES

Product group	Tyres
Item number	15772700
Valid tyre size	21.00 - 35
LI / SI / PR	36 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Rock Grip



Notes and features

- The Rock Grip Port (IND-4) from BKT is an earthmoving tyre with extra deep and robust tread pattern lugs, especially for use in ports.
- The strong casing with the low-wear tread compound provides a long service life, even wear and high stability.
- Most suitable for use on container stackers, reach stackers and similar vehicles.
- Only permitted for mounting on standard flat base rim.



Technical Informations

Item number	15772700
EAN	8903094015580
Valid tyre size	21.00 - 35
LI / SI / PR	36 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rock Grip
TRA Code	E4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	605,33
Recommended rim size	15.00/3.0
Maximum air pressure [bar].	7,50
Section width (mm)	580
Outer diameter of tyre [mm].	2040
Stat. radius (SLR) [mm]	943
Rolling circumference [mm].	6068
Tread depth (mm)	60,0
Number of lugs	32x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	12850	50		5,50	
	23000	10		7,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.