

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 15775005       |
| Valid tyre size | 240 / 70 R 16  |
| LI / SI / PR    | 107 A8 / 107 B |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Ridemax IT 696 |





## Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.



## **Technical Informations**

| Item number                  | 15775005       |
|------------------------------|----------------|
| EAN                          | 8903094067503  |
| Valid tyre size              | 240 / 70 R 16  |
| LI / SI / PR                 | 107 A8 / 107 B |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Ridemax IT 696 |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| Nettogewicht [kg] (gültig)   | 22,00          |
| Recommended rim size         | W8             |
| Permitted rim size           | W9             |
| Maximum air pressure [bar].  | 2,80           |
| Section width (mm)           | 244            |
| Outer diameter of tyre [mm]. | 742            |
| Stat. radius (SLR) [mm]      | 343            |
| Rolling circumference [mm].  | 2226           |
| Tread depth (mm)             | 20,5           |
| E-Ready                      | No             |

## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 107 A8 | 975                | 40           |               | 2,80                        |              |
| 107 B  | 975                | 50           |               | 2,80                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.