

## TYRES

Product group	Tyres
Item number	15775020
Valid tyre size	300 / 80 R 24
LI / SI / PR	133 A8 / 128 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

## Technical Informations

Item number	15775020
EAN	8903094033881
Valid tyre size	300 / 80 R 24
Alternative size 1	11.2R24
LI / SI / PR	133 A8 / 128 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,30
Recommended rim size	DW10
Maximum air pressure [bar].	3,20
Section width (mm)	295
Outer diameter of tyre [mm].	1090
Stat. radius (SLR) [mm]	501
Rolling circumference [mm].	3296
Tread depth (mm)	23,0
Number of lugs	42x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		3,20	
128 D	1800	65		3,20	