

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15775030 |
| Valid tyre size | 340 / 80 R 24 |
| LI / SI / PR | 140 A8 / 135 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Ridemax IT 696 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15775030 |
| EAN | 8903094033843 |
| Valid tyre size | 340 / 80 R 24 |
| Alternative size 1 | 12.4R24 |
| LI / SI / PR | 140 A8 / 135 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Ridemax IT 696 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 63,68 |
| Recommended rim size | DW11 |
| Permitted rim size | W10, DW10, W12 |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 343 |
| Outer diameter of tyre [mm]. | 1154 |
| Stat. radius (SLR) [mm] | 521 |
| Rolling circumference [mm]. | 3444 |
| Tread depth (mm) | 25,0 |
| Number of lugs | 42x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 140 A8 | 2500 | 40 | | 3,20 | |
| 135 D | 2180 | 65 | | 3,20 | |