Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15775045
Valid tyre size	460 / 70 R 24
LI / SI / PR	157 A8 / 152 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Ridemax IT 697



Notes and features

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications.
- It is particularly suitable for state-of-the-art contractors in winter operations.
- The tyre offers excellent grip in the field on snow and ice, even without snow chains.
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions.
- The strong casing ensures durability and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15775045
EAN	8903094067039
Valid tyre size	460 / 70 R 24
LI / SI / PR	157 A8 / 152 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Ridemax IT 697
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	95,50
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	465
Outer diameter of tyre [mm].	1254
Stat. radius (SLR) [mm]	571
Rolling circumference [mm].	3772
Tread depth (mm)	25,0
Number of lugs	29x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		3,20	
152 D	3550	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.