

## TYRES

Product group	Tyres
Item number	15775048
Valid tyre size	500 / 70 R 24
LI / SI / PR	157 A8 / 152 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

## Technical Informations

Item number	15775048
EAN	8903094067862
Valid tyre size	500 / 70 R 24
LI / SI / PR	157 A8 / 152 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	115,20
Recommended rim size	DW16L
Permitted rim size	DW15L, DW18L
Maximum air pressure [bar].	3,20
Section width (mm)	503
Outer diameter of tyre [mm].	1310
Stat. radius (SLR) [mm]	602
Rolling circumference [mm].	3954
Tread depth (mm)	29,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		3,20	
152 D	3550	65		3,20	