

TYRES

Product group	Tyres
Item number	15775050
Valid tyre size	400 / 80 R 28
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

Technical Informations

Item number	15775050
EAN	8903094039227
Valid tyre size	400 / 80 R 28
Alternative size 1	14.9R28
LI / SI / PR	151 A8 / 146 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	96,57
Recommended rim size	W13
Permitted rim size	W12, W14L
Maximum air pressure [bar].	3,20
Section width (mm)	404
Outer diameter of tyre [mm].	1352
Stat. radius (SLR) [mm]	615
Rolling circumference [mm].	4048
Tread depth (mm)	27,0
Number of lugs	45x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,20	
146 D	3000	65		3,20	