

TYRES

Product group	Tyres	
Item number	15775085	
Valid tyre size	480 / 80 R 38	
LI / SI / PR	166 A8 / 161 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	Ridemax IT 696	





Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.



Technical Informations

Item number 15775085 EAN 8903094033867 Valid tyre size 480 / 80 R 38 Alternative size 1 18.4R38 LI / SI / PR 166 A8 / 161 D TL/TT TL Brand BKT Tread pattern Ridemax IT 696 Antistatic No
Valid tyre size 480 / 80 R 38 Alternative size 1 18.4R38 LI / SI / PR 166 A8 / 161 D TL/TT TL Brand BKT Tread pattern Ridemax IT 696
Alternative size 1 18.4R38 LI / SI / PR 166 A8 / 161 D TL/TT TL Brand BKT Tread pattern Ridemax IT 696
LI / SI / PR 166 A8 / 161 D TL/TT TL Brand BKT Tread pattern Ridemax IT 696
TL/TT TL Brand BKT Tread pattern Ridemax IT 696
Brand BKT Tread pattern Ridemax IT 696
Tread pattern Ridemax IT 696
Antistatic No
Tyre colour Black
ECE regulation number ECE 106
Nettogewicht [kg] (gültig) 163,59
Recommended rim size W15L
Permitted rim size W16L
Maximum air pressure [bar]. 3,20
Section width (mm) 479
Outer diameter of tyre [mm]. 1733
Stat. radius (SLR) [mm] 780
Rolling circumference [mm]. 5213
Tread depth (mm) 29,0
Number of lugs 48x2
E-Ready No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		3,20	
161 D	4625	65		3,20	