

TYRES

Product group	Tyres
Item number	15775140
Valid tyre size	480 / 65 R 28
LI / SI / PR	154 A8 / 149 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 697



Bohnenkamp
Moving Professionals



Notes and features

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications.
- It is particularly suitable for state-of-the-art contractors in winter operations.
- The tyre offers excellent grip in the field on snow and ice, even without snow chains.
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions.
- The strong casing ensures durability and a long service life.

Technical Informations

Item number	15775140
EAN	8903094062720
Valid tyre size	480 / 65 R 28
LI / SI / PR	154 A8 / 149 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 697
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	105,00
Recommended rim size	DW15L
Maximum air pressure [bar].	3,20
Section width (mm)	480
Outer diameter of tyre [mm].	1335
Stat. radius (SLR) [mm]	615
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4088
Tread depth (mm)	25,0
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40		3,20	
149 D	3250	65		3,20	