

## **TYRES**

Product group	Tyres	
Item number	15775230	
Valid tyre size	650 / 65 R 38	
LI / SI / PR	175 A8 / 170 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	Ridemax IT 697	





## Notes and features

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications.
- It is particularly suitable for state-of-the-art contractors in winter operations.
- The tyre offers excellent grip in the field on snow and ice, even without snow chains.
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions.
- The strong casing ensures durability and a long service life.



## **Technical Informations**

Item number	15775230
EAN	8903094055418
Valid tyre size	650 / 65 R 38
LI / SI / PR	175 A8 / 170 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Ridemax IT 697
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	228,87
Recommended rim size	DW20B
Permitted rim size	DW18L
Maximum air pressure [bar].	3,20
Section width (mm)	645
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	823
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5514
Tread depth (mm)	30,5
Number of lugs	30x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A8	6900	40		3,20	
170 D	6000	65		3,20	