Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15775235	
Valid tyre size	650 / 85 R 38	
LI / SI / PR	183 A8 / 178 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Ridemax IT 697	



Notes and features

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications.
- It is particularly suitable for state-of-the-art contractors in winter operations.
- The tyre offers excellent grip in the field on snow and ice, even without snow chains.
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions.
- The strong casing ensures durability and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15775235
EAN	8903094066322
Valid tyre size	650 / 85 R 38
LI / SI / PR	183 A8 / 178 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Ridemax IT 697
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	328,50
Recommended rim size	DW23B
Permitted rim size	DW20B, DW21B
Maximum air pressure [bar].	3,20
Section width (mm)	709
Outer diameter of tyre [mm].	2071
Stat. radius (SLR) [mm]	974
Rolling circumference [mm].	6280
Tread depth (mm)	32,5
Number of lugs	36x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A8	8750	40		3,20	
178 D	7500	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.