

## TYRES

Product group	Tyres
Item number	15775280
Valid tyre size	540 / 80 R 42
LI / SI / PR	173 A8 / 168 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

## Technical Informations

Item number	15775280
EAN	8903094062409
Valid tyre size	540 / 80 R 42
Alternative size 1	20.8R42
LI / SI / PR	173 A8 / 168 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	221,12
Recommended rim size	W18L
Permitted rim size	W16L
Maximum air pressure [bar].	3,20
Section width (mm)	560
Outer diameter of tyre [mm].	1931
Stat. radius (SLR) [mm]	879
Rolling circumference [mm].	5875
Tread depth (mm)	30,5
Number of lugs	51x2
Tyre capacity 75% [ltr.]	601.27
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		3,20	
168 D	5600	65		3,20	