

## **TYRES**

Product group	Tyres
Item number	15775990
Valid tyre size	5.00 R 8
LI / SI / PR	111 A5
TL/TT	TL
Brand	ВКТ
Tread pattern	Liftmax LM 81



## Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel carcass and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial carcass absorbs unevenness of the surface, thereby increasing driving comfort and safety of the operator and preventing fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.



## **Technical Informations**

Item number	15775990
EAN	8903094059423
Valid tyre size	5.00 R 8
LI / SI / PR	111 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	10,41
Recommended rim size	3.00D
Maximum air pressure [bar].	10,00
Section width (mm)	138
Outer diameter of tyre [mm].	471
Tread depth (mm)	23,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
111 A5	1090	25	Steering wheel	10,00	
	1415	25	Load wheel	10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.