

TYRES

Product group	Tyres
Item number	15775995
Valid tyre size	180 / 70 R 8
LI / SI / PR	120 A8
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel carcass and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial carcass absorbs unevenness of the surface, thereby increasing driving comfort and safety of the operator and preventing fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Technical Informations

Item number	15775995
EAN	8903094067596
Valid tyre size	180 / 70 R 8
Alternative size 1	18x7R8
LI / SI / PR	120 A8
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	11.42
Recommended rim size	4.33R
Maximum air pressure [bar].	10,00
Section width (mm)	170
Outer diameter of tyre [mm].	453
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1650	40	Load wheel	10,00	
	2145	25	Load wheel	10,00	
	1650	25	Steering wheel	10,00	