

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15776018 |
| Valid tyre size | 225 / 75 R 15 |
| LI / SI / PR | 149 A5 |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Liftmax LM 81 |



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel carcass and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial carcass absorbs unevenness of the surface, thereby increasing driving comfort and safety of the operator and preventing fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15776018 |
| EAN | 8903094052967 |
| Valid tyre size | 225 / 75 R 15 |
| Alternative size 1 | 28x9R15 |
| LI / SI / PR | 149 A5 |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Liftmax LM 81 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 32,63 |
| Recommended rim size | 7.00 |
| Maximum air pressure [bar]. | 10,00 |
| Section width (mm) | 226 |
| Outer diameter of tyre [mm]. | 712 |
| Tread depth (mm) | 24,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|----------------|--------------------------|--------------|
| 149 A5 | 3250 | 25 | Steering wheel | 10,00 | |
| | 4225 | 25 | Load wheel | 10,00 | |