

TYRES

Product group	Tyres
Item number	15776035
Valid tyre size	12.00 R 20
LI / SI / PR	176 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81



Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel casing and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial casing absorbs ground unevenness and thus increases high ride comfort and the operator's safety and prevents fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Technical Informations

Item number	15776035
EAN	8903094053025
Valid tyre size	12.00 R 20
LI / SI / PR	176 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	119,54
Recommended rim size	8.50
Permitted rim size	8.0, 9.0
Maximum air pressure [bar].	10,00
Section width (mm)	314
Outer diameter of tyre [mm].	1134
Tread depth (mm)	38,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A5	7100	25	Steering wheel	10,00	
	9230	25	Load wheel	10,00	