

## TYRES

Product group	Tyres
Item number	15776060
Valid tyre size	14.00 R 24
LI / SI / PR	193 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81



## Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel casing and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial casing absorbs ground unevenness and thus increases high ride comfort and the operator's safety and prevents fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

## Technical Informations

Item number	15776060
EAN	8903094058549
Valid tyre size	14.00 R 24
LI / SI / PR	193 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	240,78
Recommended rim size	10.00W
Permitted rim size	10.0, 10.00WA
Maximum air pressure [bar].	10,00
Section width (mm)	388
Outer diameter of tyre [mm].	1415
Tread depth (mm)	62,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
193 A5	11500	25	Steering wheel	10,00	
	14950	25	Load wheel	10,00	