

TYRES

Product group	Tyres
Item number	15776080
Valid tyre size	16.00 R 25
LI / SI / PR	200 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81



Technical Informations

Item number	15776080
EAN	8903094069071
Valid tyre size	16.00 R 25
LI / SI / PR	200 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	348,64
Recommended rim size	11.25/2.0

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Permitted rim size	13.00/2.0
Maximum air pressure [bar].	10,00
Section width (mm)	440
Outer diameter of tyre [mm].	1530
Tread depth (mm)	70,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
200 A5	14000	25	Steering wheel	10,00	
	18200	25	Load wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.