

TYRES

Product group	Tyres
Item number	15785300
Valid tyre size	280 / 75 R 22.5
LI / SI / PR	168 A8
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PT 93



Notes and features

- The BKT Portmax PT93 was developed for use on terminal tractors.
- Its antistatic rubber compound is extremely wear resistant, even in tough operating conditions.
- The special tread pattern provides good grip and very high manoeuvrability.
- The tyre is suitable for long-term use in port and logistics terminals.

Technical Informations

Item number	15785300
EAN	8903094053902
Valid tyre size	280 / 75 R 22.5
LI / SI / PR	168 A8
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PT 93
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	73,17
Recommended rim size	8.25
Permitted rim size	9.00
Maximum air pressure [bar].	10,00
Section width (mm)	282
Outer diameter of tyre [mm].	998
Tread depth (mm)	31,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		10,00	