

TYRES

Product group	Tyres
Item number	15785328
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	170 A8
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PT 93



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Portmax PT93 was developed for use on terminal tractors.
- Its antistatic rubber compound is extremely wear resistant, even in tough operating conditions.
- The special tread pattern provides good grip and very high manoeuvrability.
- The tyre is suitable for long-term use in port and logistics terminals.

Technical Informations

Item number	15785328
EAN	8903094067855
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	170 A8
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PT 93
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	71,96
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	10,00
Section width (mm)	307
Outer diameter of tyre [mm].	965
Tread depth (mm)	26,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A8	6000	40		10,00	