

## **TYRES**

Product group	Tyres	
Item number	15785330	
Valid tyre size	310 / 80 R 22.5	
LI / SI / PR	175 A8	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Portmax PT 93	



## Notes and features

- The BKT Portmax PT93 was developed for use on terminal tractors.
- Its antistatic rubber compound is extremely wear resistant, even in tough operating conditions.
- The special tread pattern provides good grip and very high manoeuvrability.
- The tyre is suitable for long-term use in port and logistics terminals.



## **Technical Informations**

Item number	15785330
EAN	8903094057764
Valid tyre size	310 / 80 R 22.5
LI / SI / PR	175 A8
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PT 93
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	88,04
Recommended rim size	9.00
Maximum air pressure [bar].	10,00
Section width (mm)	308
Outer diameter of tyre [mm].	1070
Tread depth (mm)	29,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A8	6900	40		10,00	
	7760	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.